

NORDIC ID SAMPO S1

NORDIC ID SAMPO S1

Nordic ID Sampo S1 is a fixed UHF RFID reader with an integrated antenna, which come with a flat design.

Nordic ID Sampo S1 is a basic but powerful RFID reader and writer with USB interface for communication and power.



















PoUSB

Tapping Sensor

LED indicators

Buzzer

| UHF RFID | |
|-----------------------------|--|
| Supported standard | ISO 18000-63 (EPC Class 1 Gen2v2) AES authentication in accordance with ISO/IEC 29167-10 supported |
| Frequency band | ETSI 865.6-867.6 MHz or FCC/IC 902-928 MHz |
| Regulatory | CE ETSI EN 302 208, CE ETSI EN 301 489, FCC part 15.247 IC RSS-210, Safety IEC 62368-1:2019 ed. 3 |
| Typical reading speed | 200 tags / sec in DRM mode |
| RFID radiated power | Adjustable in 1 dB steps |
| | +30dBm (1 W) ERP External antenna ports (optional): +27dBm (500 mW) |
| Integrated antenna features | 8 dBic circular polarized, Beam width: 80° |
| | Nominal reading distance: 5 m (16 ft) |
| USER INTERFACE | |
| Signals and indicators | LEDs: Power, RFID on, RFID read and Communication |
| | Buzzer for sound indications Light sensor and tapping sensor for triggering reading |
| CONNECTIVITY | Light seriou and tapping seriou for triggering reduing |
| USB | Bus powered USB 2.0 device (appears as a serial port) |
| | Bus power car OSB 2.0 device (appears as a serial port) |
| POWER | |
| External Power Supply | USB or 240/110V AC/DC adapter |
| Operating Power | 3 W |
| SIZE AND WEIGHT | |
| Dimensions | (W) 200 x (L) 260 x (H) 25 mm ((W) 7.9 x (L) 10.2 x (H) 1.0 inch) |
| Weight | 540 g / 19.0 oz |
| ENVIRONMENT | |
| Operating Temperature | -20 to 55 °C -4 to 130 °F |
| Storage Temperature | -40 to 85 °C -40 to 185 °F |
| Environmental sealing | IP20, for indoor use only |
| | |

All information is subject to change without prior notice. Availability of product variants may vary regionally.

PRODUCT HIGHLIGHTS

- Long-range and accurate RFID reading
- Power over USB or external power supply

SOFTWARE APPLICATIONS

- RFID Demo Software for testing reader capabilities
- RFID Configurator software for configuring the reader

SOFTWARE DEVELOPMENT

- Ready-to-use Nordic ID NUR API that provides full control over the reader
- Application can be written in C/C++, .NET languages and Java
- USB driver for: Windows: XP, Vista, 7, 8, 10, Linux, Android

SUITABLE APPLICATION AREAS

- Point-of-sales
- Document tracking
- Access control
- Tag programming stations
- Smart shelves and smart displays
- · Inventory management

SERVICE AND SUPPORT

- Free support during and after warranty time
 Maintenance service and extended warranty contract
- Software customization and development support
- Technology, product and integration training Technology and project consultation
- Project management services

WARRANTY

- 2 year warrantyExtendable up to 5 years











